

Ergonomic angled handles



GENERAL INFORMATION

- Pre-assembled panels and integrated door slide-locks allow for a simple and quick installation
- Perimeter compression gaskets efficiently seal and minimize air leakage
- Multiwall panels adhere to 2013 NFPA 75 flame spread and smoke development requirements
- No-threshold design prevents obstructions or tripping
- Sturdy aluminum framing
- Fully supported by floor with rack attachments for lateral stability
- Ergonomic design, with angled handles to reduce pinch points

Weights

- 172 lbs. – Clear polycarbonate
- 140 lbs. – Multiwall polycarbonate

Dimensions

- 74"-96" height
- 4.85" depth
- 36"-72" opening width

FEATURES

Panel Options

- Clear polycarbonate
 - Fully transparent
 - ASTM D-635 listed
 - 6mm thick with edge-sealing gaskets
- Multiwall polycarbonate
 - Semi-transparent
 - Flame spread index <50
 - Smoke development <450
 - ASTM E-84 and ASTM D-635 listed
 - UL 94 listed
 - 8mm thick

Aluminum Extrusion Finish Options


- Gray
- Black
- White

Hardware Options

- Standard features includes 2 spring loaded double ball door catches

INCLUDED COMPONENTS

- ContainAire® Dual Hinged Doors
- Floor and rack mounting hardware
- Installation guide



PART NUMBERS

