

SPECIFICATIONS

General Information

- Pre-assembled panels allow for a simple and quick installation
- Perimeter compression gaskets efficiently seal and minimise air leakage
- Right or Left Hinged option (defined by which side of the door the handle is located as you look at the aisle from the outside)
- Multiwall option adheres to 2013 NFPA 75 flame spread and smoke development requirements
- Supports aisle widths of 4' to 6' (122m x 1.82m) (6' (1.82m) aisle is a wider door)
- No-threshold design prevents obstructions or tripping
- Sturdy aluminum framing
- Recessed Hinges allow for tighter joints
- Fully supported by floor with rack attachments for lateral stability.

Weights

- 165 lbs (75kg) – Clear polycarbonate
- 135 lbs (61kg) – Multiwall polycarbonate

Dimensions

- 71.5" width x 86" height x 3.6" depth (182cm x 218cm x 9cm)
- 36" (91cm) max opening width.

OPTIONS

Panel Options

- Clear polycarbonate
 - Fully transparent
 - ASTM D-635 listed
 - 6mm thick with edge-sealing gaskets
- Multiwall polycarbonate
 - Semi-transparent
 - Flame spread index <50
 - Smoke development <450
 - ASTM E-84 and ASTM D-635 listed
 - UL 94 Listed
 - 6mm thick with edge-sealing gaskets.

Aluminum Extrusion Finish Options


- Clear Anodised
- Black Anodised.

Accessories

- Autocloser
- Push Plate (for use with Autocloser)
- Hold open (for use with Autocloser).


INCLUDED COMPONENTS

- ContainAire® Single Hinged Door
- Floor and rack mounting hardware
- Installation guide.



Recessed Hinge design

Allows for tighter frame fit,
reducing air leakage



PART NUMBERS

